(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 14 October 2004 (14.10.2004)

PCT

(10) International Publication Number WO 2004/088945 A1

(51) International Patent Classification⁷: H03F 1/32

H04L 27/36,

(21) International Application Number:

PCT/EP2004/050295

- (22) International Filing Date: 11 March 2004 (11.03.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0307372.3


31 March 2003 (31.03.2003) GB

- (71) Applicant (for all designated States except US): MO-TOROLA INC [US/US]; 1303 E.Algonquin Road, Schaumburg, Illinois 60196 (US).
- (71) Applicant (for BW only): MOTOROLA LIMITED [GB/GB]; Jays Close, Viables Industrial Estate, Basingstoke, Hampshire RG22 4PD (GB).

- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BEN-AYUN, Moshe [IL/IL]; Motorola Israel Limited, 3 Kremenetski Street, 67899 Tel Aviv (IL). NOCHAM, Gabriela [IL/IL]; Motorola Israel Limited, 3 Kremenetski Street, 67899 Tel Aviv (IL). ROZENTAL, Mark [IL/IL]; Motorola Israel Limited, 3 Kremenetski Street, 67899 Tel Aviv (IL).
- (74) Agent: MCCORMACK, Derek J.; Motorola European Intellectual Property Operations, Midpoint, Alencon Link, Basingstoke Hampshire RG21 7PL (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR LINEARIZATION IN A QUADRATURE TRANSMITTER



(57) Abstract: A wireless communication unit (300) comprises a linearised transmitter (325) having a forward path, a power amplifier (324) and a feedback loop, operably coupled to the power amplifier (324) and the forward path. The feedback loop comprises a loop adjustment function (442), and the forward path and feedback loop comprise quadrature circuits. A processor (322) applies a first training signal to a first quadrature circuit loop for routing through the forward path, power amplifier and feedback pat.i to determine at least one first parameter setting of the loop adjustment function (442). The processor (322) also applies a second training signal to a second quadrature circuit loop to determine at least a second parameter setting of the loop adjustment function (442). linearised transmitter integrated circuit and method of training are also described. In this manner, by provision of a first training signal applied to a first quadrature (1) circuit loop and a second training signal applied to a second quadrature (Q) circuit any loop imbalance between the digital T' and 'Q' paths around the feedback loop can be compensated for.

- TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.